High Volume digital PopUpPress® & digital EzPress®

from EzProducts International Inc.

The *digital PopUp Press*® is **automatic**; the handle and hot platen automatically pop up when the application cycle is complete. The *digital EzPress*® is a **manual press**; a buzzer will sound when the application cycle is complete and the operator must promptly lift the handle to remove the hot platen from the garment.

NEW EzWizard™ Software with Hot Platen Supercharger™ Calibrated to display the temperature with 1° accuracy and will hold platen temperature to within 1% of your pre-set value.

PRESS FEATURES

- Use to apply all bar code, text labels, emblems and mending patches
- Automatically adds additional time if the garments are damp or cold
- Operator error alert with supervisor auditing alerts when platen is too hot or cold or if handle is lifted before pre-set application time has lapsed.



power: 115VAC or 230 VAC, 50/60 Hz 200 - 400 Watts depending on Platen, no compressed air required

weight: EzPress: 15 lbs (6.4 kg) PopUpPress: 15 lbs (6.8kg) add 1lb (.5kg) for a Hot Lower Platen

size: 8" high (228 mm) x 6" wide (152 mm) x 11" deep (279 mm)

platen pressure: 120 lbs (55 kg) supervisor adjustable

temperature: digital control / display 300-425°F or 148-218°C supervisor adjustable

timer: digital control / display 1-60 seconds supervisor adjustable



mmmmm

PRICE digital PopUpPresso \$1,395 US digital EzPresso \$995 US

Choose 1 QuickChange™Lower Platen Assembly 4 Hot Upper Platens cover all Lower Platen Assemblies Add \$100 US for 230 VAC 50/60 Hz

WARRANTY

Two Year Factory Warranty on all parts and labor, 30-day Money Back Guarantee and Lifetime FREE Technical Support.

QuickChange™ Lower Platen Assemblies (un-heated) Additional 1 Add \$39 US

•					
Mini-1 Platen	.75" x 1.5" (19 mm x 38 mm)	Mini-2 Platen	1" x 1.5" (25mm x 38mm)	Mini-3 Platen	1" x 3" (25mm x 76mm)
Mini-4 Platen	1.5" x 1.5" (38mm x 38mm)	Mini-5 Platen	1.5" x3.75" (38mm x 95mm)	Mini-7 Platen	2" x 3.75" (51mm x 95mm)
Mini-9 Platen	2.5" x 3.75" (63mm x 95mm)	Standard 15" Platen 3" x 5" fixed		2 sizes of RFID Platens	

Hot Lower Platen Assemblies Add \$199 US 115VAC 50/60 Hz or Add \$249 230VAC 50 Hz

 Mini-5 Hot Lower Platen
 1.5" x3.75" (38mm x 95mm)
 Mini-7 Lower Platen
 2" x 3.75" (51mm x 95mm)

 Mini-9 Lower Platen
 2.5" x 3.75" (63mm x 95mm)
 Standard 15" Lower Platen
 3" x 5" (76mm x 127mm)

(Hot Lower Platens are **NOT** QuickChange™ Interchangeable Lower Platens)

The digital EzPress® and digital PopUp Press® are simple and easy to operate.

- Time, temperature and pressure are automatically controlled.
- Heated platen is Teflon coated to prevent glue accumulation.
- Lower platen will automatically adjust to accommodate thick and thin garments without manual platen adjustments.
- Built from powder coated steel using reliable solid state components with no springs.
- Both designed for high volume usage.
- Both are easy to maintain, you can, "repair any problem in 10 minutes."

The **EzWizard™ Software** controls the time and temperature; and monitors the entire operation of the press.

- Alerts the operator of a pending problem; such as platen temperature too hot or too cold.
- Detects a 'Cool Cycle' which occurs when labeling damp or cold fabric and automatically adds a few seconds of application time to insure that every label is always applied properly.

The **EzWizard™** also monitors common operator errors and alerts the operator to prevent improperly applied labels. The **EzWizard™** counts and stores Application Cycles and all Operator Errors for **easy training and quality control**.

POSSIBLE ERRORS & ALERTS:

Long Cycle: failure to lift the handle when the cycle was complete (EzPress®) Short Cycle: handle lifted before the application cycle was complete Cold Cycle: label applied before pre-set platen temperature

US & International Safety Certifications

TÜV SÜD America Inc, CE CAN/CSA-E60335-2-44-01:2006, UL 60335-1:2003/A11:2004 /A1:2004 EN 60335-2-44:2002



01/20